



Technical Data Sheet

Code **GEAA3S35AA-ASE**

Ing. Enea Mattei S.p.A.

PRODUCT SPECIFICATIONS

7/17/15

date

draft

revision

7/1/15

issue

Model **AC 11 LX**

Description	Air Centre unit		
Arrangement	Silenced		
Series	500	STANDARD PRODUCT	
Air End frame	M 86		
Version	n.a.		
OIL cooling medium	Air		
AIR cooling medium	Air		
Modulation	Yes		
Decompression	Yes		
Receiver	n.a.		
Inlet nominal pressure	ISO 1217	psi (a)	14.5
Inlet nominal temperature	ISO 1217	°F	68
Relative humidity	ISO 1217	%	0
Motor nominal speed	ISO 1217	rpm	1800
Nominal working pressure		psi (g)	108 (LX)
Maximum working pressure		psi (g)	116
Nominal delivery	(1)	cfm	69.8
Terminals absorbed power	(2) (6)	kW	14.80
Terminals unload absorbed power		Kw	3.63
Noise level (max)	ISO 2151 - @1 mt	dBA	67
Oil carry over		ppm	3
Total heat recovery (up to ...)		%	95
Oil circuit capacity		gallons	1

PERFORMANCES

psi (g)	72.5		87		102		116		131		145		160		174	
	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW
	70.7	12.17	70.3	13.24	70.0	14.30	-	-	-	-	-	-	-	-	-	-

ELECTRICAL CHARACTERISTICS

Electric certification					CEI			
Starting type					Star-Delta			
Voltage -- Frequency -- Phases					V / Hz / Ph			
Auxiliary circuit tension					V			
Nominal absorbed current					A			
Minimum supply cables section (33 ft.)					AWG			

MAIN MOTOR

Nominal power input					kW / HP			
Efficiency class					IE3			
Efficiency					%			
Poles					4			
Protection index					IP			
Insulation class					F			

COOLING

Maximum ambient temperature					°F			
Minimum ambient temperature					°F			
Outlet AIR temperature					(5) °F			
OIL maximum temperature					°F			
OIL minimum temperature					°F			
Fan type					Axial			
Cooling AIR flow (minimum)					(3) cfm			
Cooling AIR flow (maximum)					(4) cfm			
Heat Removal Oil and Aftercooler					(4) Btu/hr			
Fan residual head (minimum)					(3) Pa			
Fan residual head (maximum)					(4) Pa			
Fan absorbed power (minimum)					(3) kW			
Fan absorbed power (maximum)					(4) kW			
WATER flow					gpm			
Water INLET temperature					°F			
Water OUTLET maximum temperature					°F			
Water minimum suggested pressure					psi (g)			
Thermal recoverable power					Kcal			

DRYER

Refrigerant gas					-			
Dew point (pressure)					°F			
Absorbed power					kW			
Regeneration air percentage					%			
Supply: Voltage - frequency - phases					V / Hz / Ph			

DIMENSIONS

AIR outlet connection					Rp 3/4"			
Condensate separator drain connection					Rp 3/4"			
Condensate drain connection					10 mm (male)			
Condensate DRYER drain connection					-			
Receiver condensate drain connection					-			
INLET-OUTLET water connections					-			
Storage AIR receiver volume					gallons			
Width					inch			
Length					inch			
Height					inch			
Weight					lbs			

NOTES

- (1) - According to ISO 1217 - Annex C (fixed speed) & Annex E (variable speed)
- (2) - Fan included (@ first speed if available) - Dryer input power excluded
- (3) - Fan @ lower speed (OPTIMA @ min speed)
- (4) - Fan @ faster speed (Optima : fan @50Hz)
- (5) - @ reference conditions
- (6) - OPTIMA @ 1500 rpm and 102 psi