



Technical Data Sheet

Code **GEAEPS350A-ASE**

Ing. Enea Mattei S.p.A.

PRODUCT SPECIFICATIONS

6/10/15

date

draft

revision

1/28/15

issue

Model **AC 7 HHX**

Description	Air Centre unit		
Arrangement	Silenced		
Series	500	STANDARD PRODUCT	
Air End frame	M 86		
Version	n.a.		
OIL cooling medium	Air		
AIR cooling medium	Air		
Modulation	Yes		
Decompression	Yes		
Receiver	n.a.		
Inlet nominal pressure	ISO 1217	psi (a)	14.5
Inlet nominal temperature	ISO 1217	°F	68
Relative humidity	ISO 1217	%	0
Motor nominal speed	ISO 1217	rpm	1800
Nominal working pressure		psi (g)	181 (HH)
Maximum working pressure		psi (g)	188
Nominal delivery	(1)	cfm	42
Terminals absorbed power	(2) (6)	kW	11.11
Terminals unload absorbed power		Kw	2.2
Noise level (max)	ISO 2151 - @1 mt	dBA	67
Oil carry over		ppm	3
Total heat recovery (up to ...)		%	95
Oil circuit capacity		gallons	1

PERFORMANCES

psi (g)	72.5		87		102		116		131		145		160		174	
	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW	cfm	kW
	-	-	-	-	-	-	-	-	42.4	9.83	42.2	10.32	42.0	10.72	41.9	11.01

ELECTRICAL CHARACTERISTICS

Electric certification			CEI	
Starting type			Star-Delta	
Voltage -- Frequency -- Phases			V / Hz / Ph	
Auxiliary circuit tension			208/60/3	230/60/3
Nominal absorbed current	(6)		110	110
Minimum supply cables section (33 ft.)			42.9	38.8
			8	10
			10	10

MAIN MOTOR

Nominal power input	kW / HP	7 / 10
Efficiency class		IE3
Efficiency	%	91.7
Poles		4
Protection index	IP	55
Insulation class		F

COOLING

Maximum ambient temperature	°F	104
Minimum ambient temperature	°F	34
Outlet AIR temperature	(5) °F	< 86
OIL maximum temperature	°F	248
OIL minimum temperature	°F	176
Fan type		Axial
Cooling AIR flow (minimum)	(3) cfm	-
Cooling AIR flow (maximum)	(4) cfm	1118
Heat Removal Oil and Aftercooler	(4) Btu/hr	37918
Fan residual head (minimum)	(3) Pa	-
Fan residual head (maximum)	(4) Pa	20
Fan absorbed power (minimum)	(3) kW	-
Fan absorbed power (maximum)	(4) kW	0.18
WATER flow	gpm	-
Water INLET temperature	°F	-
Water OUTLET maximum temperature	°F	-
Water minimum suggested pressure	psi (g)	-
Thermal recoverable power	Kcal	-

DRYER

Refrigerant gas		-
Dew point (pressure)	°F	-
Absorbed power	kW	-
Regeneration air percentage	%	-
Supply: Voltage - frequency - phases	V / Hz / Ph	-

DIMENSIONS

AIR outlet connection		Rp 3/4"
Condensate separator drain connection		Rp 3/4"
Condensate drain connection		10 mm (male)
Condensate DRYER drain connection		-
Receiver condensate drain connection		-
INLET-OUTLET water connections		-
Storage AIR receiver volume	gallons	n.a.
Width	inch	24
Length	inch	49
Height	inch	41
Weight	lbs	485

NOTES

- (1) - According to ISO 1217 - Annex C (fixed speed) & Annex E (variable speed)
- (2) - Fan included (@ first speed if available) - Dryer input power excluded
- (3) - Fan @ lower speed (OPTIMA @ min speed)
- (4) - Fan @ faster speed (Optima : fan @50Hz)
- (5) - @ reference conditions
- (6) - OPTIMA @ 1500 rpm and 102 psi